



## THERMAL SECURITY CAMERA

# FLIR Elara™ FC-Series 0

The Elara™ FC-Series 0 thermal security camera is one of FLIR's premium thermal security cameras for perimeter protection. The Elara FC-Series 0 integrates with external video analytics devices, such as FLIR's TRK or third party solutions, to classify human or vehicular intrusions. The Elara FC-Series 0 also offers a wide range of high-performance lenses, with a choice of resolutions, offering greater flexibility for tailoring security systems to specific site conditions.

[www.flir.com/security](http://www.flir.com/security)



### INTEGRATES WITH ANALYTICS

The FC-Series 0 is an ideal camera for integrating with external video analytics systems.

- Fully integrated and certified to work with third party video management systems
- Supports open standard, ONVIF-compliant
- Advanced integration features, such as thermal configuration and alarm management, with FLIR's United VMS



### INDUSTRY-LEADING IMAGE QUALITY

Superior thermal image quality in low-contrast conditions.

- Superior image quality in extreme environments
- Custom AGCs provide unmatched image contrast
- Digital Detail Enhancement (DDE) produces sharp edges that improve performance of analytics



### HIGH-PERFORMANCE LENSES

Choose from a wide range of high-performance lenses for optimal detection ranges in all conditions.

- Choose from 17 high performance lenses suitable for any perimeter or open area, including QVGA from 4° to 69° fields of view and VGA from 8° to 90° fields of view
- High-performance optics deliver crisp, clean thermal video
- High analytic ranges reduce number of cameras and total cost of ownership (TCO)

## SPECIFICATIONS

Thermal Camera Specifications		
Model	Elara FC-3XX 0	Elara FC-6XX 0
Array Format	320 × 240	640 × 480
Detector Type	Uncooled VOx Microbolometer	
Spectral Range	7.5 μm – 13.5 μm	
Effective Resolution	76800	307200
Pixel Pitch	FC-369 0 FC-344 0 FC-332 0 Other models	34 μm 34 μm 34 μm 17 μm
Thermal Frame Rate	NTSC: 30 Hz, PAL: 25 Hz / 8.3 Hz	
E-Zoom	4x continuous E-Zoom	
Focus	Athermalized, focus-free	
Sensitivity	< 35 mK for F# 1.0 optics	
Video		
Composite Video NTSC or PAL	Hybrid system with IP & analog video, Dynamic NTSC or PAL settings	
Analog Video Output Composite	1x Vp-p (PAL or NTSC), 1x BNC 75 Ω	
Video Compression	Two independent channels of H.264 (Restricted VBR and CBR, 10 kbps – 4 Mbps, MPEG4, and MJPEG)	
Streaming Resolution	D1: 720 × 576, 4CIF: 704 × 576, Native: 640 × 512, Q-Native: 320 × 256, CIF: 352 × 288, QCIF: 176 × 144	
Thermal AGC Modes Features	Brightness, contrast, sharpness, gray shade compression, gamma, smart screen balance	
Thermal AGC Region of Interest (ROI)	Default, presets and user-definable to ensure optimal image quality of subjects of interest	
Image Uniformity Optimization	Automatic Flat Field Correction (FFC); Thermal and Temporal Triggers	
SD Card Snapshot Capture	Support for 32 GB SD Card (sold separately)	
System Integration		
Ethernet	10/100 Mbps	
External Analytics Compatible	Yes	
Control Input/Output	1x dry contact in; 1x relay out (rated load .025 A at 5 VDC)	
Network APIs	FLIR SDK, FLIR CGI, ONVIF Profile S	
Network		
Supported Protocols	IPv4, HTTP, Bonjour, UPnP, DNS, NTP, RTCP, TCP, UDP, ICMP, IGMP, DHCP, ARP, SCP, FTP, RTP/RTSP, Unicast/Multicast, TCP/IP, HTTP, IEEE 802.1X, SNMP	
General		
Weight without sunshield	1.8 – 2.2 kg (4 – 4.75 lb)	
Weight with sunshield	2.2 – 2.5 kg (4.75 – 5.5 lb)	
Dimensions (L, W, H) without sunshield	259 × 114 × 106 mm (10.2" × 4.5" × 4.2")	
Dimensions (L, W, H) with sunshield	282 × 129 × 115 mm (11.1" × 5.1" × 4.5")	
Power Consumption (heater off)	< 5.5 W to < 8 W (varies by model)	
Power Consumption (heater at 100%)	< 25 W to < 32 W (varies by model)	
Surge Immunity on AC Power Lines	CE: EN55032 Class A; FCC 47 CFR Part 15, Subpart B, Class A (within CISPR 22:2008 Class A limits)	
Surge Immunity on Signal Lines	EN 55024: 2010 and 55032: 2010 to 4.0kV on AC aux power lines; EN 50130-4:2011; IEC 62599-2:2010	

Cyber Security	
IEEE 802.1x TLS/HTTPS User authentication Access control via firewall Digest authentication	
Environmental	
IP Rating (Dust/Water Ingress)	IP66 & IP67
Operating Temp. Range	-50°C to 70°C (-58°F to 158°F)
Storage Temp. Range	-50°C to 85°C (-58°F to 185°F)
Humidity	0 – 95% relative humidity
Shock	MIL-STD-810G "Transportation"
Vibe	IEC 60068-2-27
Anti-Icing	MIL-STD-810 F, Method 521.2 - 6 mm ice, 120 minutes with POE+, 4 mm ice with POE af FC-304, FC-305, FC-610 & FC-608 with Cold Weather kit
Warranty & Regulatory	
Approvals	CE: EN55032 Class A; FCC 47 CFR Part 15, Subpart B, Class A (within CISPR 22:2008 Class A limits)
Certifications	IEC 60068-2-1:2007; IEC 60068-2-2:2007; ISTA-1A (Handling)
Compliance	RoHS Directive 2011/65/EU; WEEE 2012/19/EU
Warranty	Camera: 3 years; Sensor: 10 years

Optical characteristics			
Model	FOV, F#, Focal Length	Model	F# / FOV / Focal Length
FC-396 0	69° × 56°, f/1.4, 9 mm	FC-690 0	90° × 69°, f/1.2, 7.5 mm
FC-344 0	44° × 36°, f/1.0, 13 mm	FC-669 0	69° × 56°, f/1.4, 9 mm
FC-332 0	32° × 26°, f/1.0, 19 mm	FC-644 0	44° × 36°, f/1.0, 13 mm
FC-324 0	24° × 18°, f/1.0, 13 mm	FC-632 0	32° × 26°, f/1.0, 19 mm
FC-317 0	17° × 13°, f/1.0, 19 mm	FC-625 0	25° × 20°, f/1.1, 25 mm
FC-313 0	13° × 10°, f/1.1, 25 mm	FC-617 0	17° × 14°, f/1.1, 35 mm
FC-309 0	9.2° × 7°, f/1.1, 35 mm	FC-610 0	10° × 8.2°, f/1.25, 60 mm
FC-305 0	5.4° × 4.1°, f/1.25, 60 mm	FC-608 0	8.6° × 6.6°, f/1.1, 75 mm
FC-304 0	4.3° × 3.3°, f/1.1, 75 mm		

Specifications are subject to change without notice. For the most up-to-date specs, go to [www.flir.com](http://www.flir.com)

**CORPORATE HEADQUARTERS**  
FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
USA  
PH: +1 866.477.3687

**GOLETA**  
FLIR Systems, Inc.  
6769 Hollister Ave.  
Goleta, CA 93117  
USA  
PH: +1 805.690.6600

[www.flir.com](http://www.flir.com)  
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2020 FLIR Systems, Inc. All rights reserved. 06/20

20-0884-SEC



The World's Sixth Sense®